

## DATA SHEET – PRECON KERBS, PRECON EDGINGS

### PRODUCT SPECIFICATIONS

Our British Standard Kerb, Channels and Edgings are manufactured to the dimensions required by BS EN 1340:2003 to achieve a consistent, strong and durable product. Available with a wide range of ancillary products and in a natural shade of concrete these products are suitable for a wide range of both Commercial and Domestic project applications.

#### Product Type:

Semi Dry Pressed and Vibrated Concrete

**Manufactured and Tested to:** BS EN 1340:2003

#### Surface Finish:

Smooth (some ancillaries Pimpled)

#### Bending Strength:

Characteristic bending strength of class 3 (6.0MPa with no individual result less than 4.8MPa)

#### Polished Slip Skid Resistance Value (USRV):

Potential for slip – low (wet/dry)

#### Durability (Freeze Thaw):

≤ 1.0 kg/m<sup>2</sup> as a mean with no individual value > 1.5 kg/m<sup>2</sup>

**Abrasion Resistance (Wide Wheel Test):**

Class 4 <= 20mm

#### Tolerances on Work Dimensions:

+/- 3mm

#### Material Density:

2250kg/m<sup>3</sup>

#### Application/Suitability:

Laid in accordance with BS 7533-6:1999

#### Emission of Asbestos:

No content

#### External Fire Performance:

Deemed to satisfy

### STANDARD DIMENSIONS\*

<b>HB2 Half Battered Kerb</b> 125x255x915	<b>BN3 Bullnose Kerb</b> 125x150x915
<b>HB3 Half Battered Kerb</b> 125x150x915	<b>Round/Flat Topped Edging</b> 150x50x915
<b>BN2 Bullnose Kerb</b> 125x255x915	<b>Round/Flat Topped Edging</b> 200x50x915

\*Also available in other nominal sizes, radiuses and profiles.