

DATA SHEET - PRECON KERBS, PRECON EDGINGS

PRODUCT SPECIFICATIONS

Our British Standard Kerb, Channels and Edgings are manufactured to the dimensions required by BS EN 1340:2003 using hydraulic pressing to achieve a consistent, strong and durable product. Available with a wide range of ancillary products and in a natural shade of grey concrete these products are suitable for a wide range of both Commercial and Domestic project applications.

Product Type:

Hydraulically
Pressed Concrete

Manufactured and Tested to: BS EN 1340:2003

Surface Finish:

Smooth (some ancillaries Pimped)

Bending Strength:

Characteristic bending strength of class 3 (6.0MPa with no individual result less than 4.8MPa)

Polished Slip Skid Resistance Value (USRV):

Potential for slip – low (wet/dry)

Durability (Freeze Thaw):

≤ 1.0 kg/m² as a mean with no individual value > 1.5 kg/m²

Abrasion Resistance (Wide Wheel Test):

Class 4 < /= 20mm

Tolerances on Work Dimensions:

+/- 3mm

Material Density:

2250kg/m³

Application/Suitability:

Laid in accordance with BS 7533-6:1999

Emission of Asbestos:

No content

External Fire Performance:

Deemed to satisfy

STANDARD DIMENSIONS*

HB2 Half Battered Kerb 125x255x915	BN3 Bullnose Kerb 125x150x915
HB3 Half Battered Kerb 125x150x915	Round/Flat Topped Edging 150x50x915
BN2 Bullnose Kerb 125x255x915	Round/Flat Topped Edging 200x50x915

*Also available in other nominal sizes, radiuses and profiles.