

- Dimensionally accurate tolerances.
- · Straight line.
- Manufactured and supplied from our plant in Coatbridge, Scotland.
- Eco friendly 60% recovered aggregate.
- Part of a range of complimentary products.
- · Readily available.
- Suitable for a wide range of domestic and commercial projects.
- · Highly durable.
- Manufactured to BS EN 1340:2003.

PRODUCT NAME	CODE	UNIT WEIGHT (KG)	PACK SIZE	PACK WEIGHT (T)	COLOUR
150x50x915 Flat Top Edging	6x2FT	15	15no	0.23	Natural
200x50x915 Flat Top Edging	8x2FT	20	15no	0.3	Natural
200x50x915 Round Top Edging	8x2RT	20	15no	0.3	Natural

MATERIAL DENSITY	DURABILITY	STRENGTH	
2350 kg/m3 (typically)	<pre><!-- Equal 1.kg/m2 as mean with no individual value --> 1.5kg/m2 (Typically <0.20kg/m2 - Non frost susceptible)</pre>	> 3.5MPa	



- Dimensionally accurate tolerances.
- · Straight line.
- Manufactured and supplied from our plant in Coatbridge, Scotland.
- Eco friendly 60% recovered aggregate.
- · Part of a range of complimentary products.
- · Readily available.
- Suitable for a wide range of domestic and commercial projects.
- · Highly durable.
- Manufactured to BS EN 1340:2003.

PRODUCT NAME	CODE	UNIT WEIGHT (KG)	PACK SIZE	PACK WEIGHT (T)	COLOUR
150x50x915 Flat Top Edging	6x2FT	15	15no	0.23	Natural
200x50x915 Flat Top Edging	8x2FT	20	15no	0.3	Natural
200x50x915 Round Top Edging	8x2RT	20	15no	0.3	Natural

MATERIAL DENSITY	DURABILITY	STRENGTH	
2350 kg/m3 (typically)	<pre><!-- Equal 1.kg/m2 as mean with no individual value --> 1.5kg/m2 (Typically <0.20kg/m2 - Non frost susceptible)</pre>	> 3.5MPa	